





Aspire Elite

Available in the following styles



Hazy Maple APX1301



Cider Horizon APX1302




Harvest Glow APX1303




Burnished Sunrise APX1304



Dewlit Amber APX1305




Dulcet Silk APX1306




Vanilla Bloom APX1307




Grey Gust APX1308



Delayed Dawn APX1309



Aged Bulwark APX1310



Static Citadel APX1311



Akita Frost APX1312

CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	100% Recycled PP 2 ply	
Machine Gauge	1/10 gauge	
Width	4 & 5 Mtrs	
Tufts Density	131,234 tufts/ m ²	BS ISO 1763:2020
Total Weight	2200g	BS ISO 8543:2020
Inserted Weight	1175g	BS ISO 8543:2020
Pile Height	8mm (±10%)	BS ISO 1766:1999
Total Thickness	11mm (±10%)	BS ISO 1765:1986
Standard Roll Length	30 linear metres	
Type of Backing	Combi-Bac®	
Classification	Class 23 - Heavy Domestic Class 32 - General Commercial	BS EN 1307:2014
	Luxury Class 3	BS EN 1307:2014
Thermal Resistance	1.30 TOG / 0.130m ² K/W TBC	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	High Radius of Char	BS 4790:1987 (2014)
Flammability	Efl -s1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12
WARRANTY		
Wear	10 years	
Stain	Bleach Cleanable	
Biological	Moth / Insect proof	
Made in UK		
CE Compliant		EN14041:2004
ISO certifications		ISO 9001, ISO 14001, ISO 45001

