

Technical Specification

Hardwearing and sustainably sourced with a Uniclic® system for faster fitting, Auralis delivers on price, quality and aesthetic. The on trend decors range from light to dark and are inspired by authentic wood types – plus with its 72 hour water resistance, Auralis really is the perfect hardflooring choice.

PRODUCT INFORMATION		PRODUCT SPECIFICATION	
Collection	Auralis		
Thickness	8mm		EN 13329+A2
Width	197mm		EN 13329+A2
Length	1205mm		EN 13329+A2
Surface	Authentic		
Quantity/weight per box (PU)	8 pieces = 1.9m² /approx 14 kg		
Quantity/weight per pallet	56 PU= 106.4 m² /approx 810 kg		
Class	32		EN13329 + A2
Abrasion Resistance	AC4		EN13329 + A2
Thickness Swelling	≤18		ISO 24336
Surface Swelling (Assembled Joint)	Qualitative Rating ≤2 (1-5) Quantative Rating ≤0,3mm		ISO 4760 (Nalfa 72h)
Resistance to Impact	Small Ball ≥12 N Large Ball ≥750mm		EN 13329+A2
Warranty Domestic/commercial	15/10 Years		
Resistance to Staining	Min.5 (group 1 and 2) Min4. (group 3)		EN 438-2_5
Surface Soundness	≥1.25 N/mm²		EN 13329+A2
Lock Strength	Length fl0,2 ≥ 1 kN/m		ISO 24334
	Width fs0,2 ≥2 kN/m		
Effect of Castor Chair	25.000 Cycles - No Damage		EN 425:2002
Effect of a Furniture Leg	No Damage		EN 424
Opening Between Elements	≤0,20mm		EN 13329+A2
Height Difference Between Elements	≤0,15mm		EN 13329+A2
Moisture Content	4-10%		EN 322
Fire Resistance	CflS1		EN 9239-1
Formaldehyde Release	E0≤1,75 1,75≤E1≤3,5 mg/m²h		EN 12460-3
Slip Resistance	DS		EN 14041:2008
Thermal Conductivity	0.148 W/(m*K) / 0.54 Tog		EN 12667:2001
Sound Rating	14dB		ISO 717-2



15
YEAR
WARRANTY

Backed with a comprehensive warranty for lifes unexpected changes



Letting you put 100% into your house move.
Zero hassle, Zero Stress, Every time.



Choosing the right flooring for each room is a breeze with our roomviewer app