

Auralis

Available in the following styles



Danira Flow
APX6201



Tirava Drift
APX6202



Delmere Grain
APX6203



Gavari Mist
APX6204



Thalyn Shore
APX6205



Neraya Sands
APX6206



Trenric Grove
APX6207



Ervale Timber
APX6208

PRODUCT INFORMATION		PRODUCT SPECIFICATION	
Collection	River		
Thickness	8mm	EN 13329+A2	
Width	197mm	EN 13329+A2	
Length	1205mm	EN 13329+A2	
Surface	Authentic		
Quantity/weight per box (PU)	8 pieces = 1.9m² /approx 14 kg		
Quantity/weight per pallet	56 PU= 106.4 m² /approx 810 kg		
Class	32	EN13329 + A2	
Abrasion Resistance	AC4	EN13329 + A2	
Thickness Swelling	≤18	ISO 24336	
Surface Swelling (Assembled Joint)	Qualitative Rating ≤2 (1-5) Quantative Rating ≤0,3mm	ISO 4760 (Nalfa 72h)	
Resistance to Impact	Small Ball ≥12 N Large Ball ≥750mm	EN 13329+A2	
Warranty Domestic/commercial	15/10 Years		
Resistance to Staining	Min. 5 (groups 1 and 2); min. 4 (group 3)	EN 438-2_5	
Surface Soundness	≥1.25 N/mm²	EN 13329+A2	
Lock Strength	Length fl0,2 ≥ 1 kN/m	ISO 24334	
	Width fs0,2 ≥2 kN/m		
Effect of Castor Chair	25,000 Cycles - No Damage	EN 425:2002	
Effect of a Furniture Leg	No Damage	EN 424	
Opening Between Elements	≤0,20mm	EN 13329+A2	
Height Difference Between Elements	≤0,15mm	EN 13329+A2	
Moisture Content	4-10%	EN 322	
Fire Resistance	Cfl-s1	EN 9239-1	
Formaldehyde Release	E0≤1,75 1,75≤E1≤3,5 mg/m²h	EN 12460-3	
Slip Resistance	DS	EN 14041:2008	
Thermal Conductivity	0.148 W/(m*K) / 0.54 Tog	EN 12667:2001	
Sound Rating	14dB	ISO 717-2	

