

Bellatour LVT flooring authentically captures the character and texture of natural materials across a range of wood and tile designs. Warm underfoot and highly durable, it also offers excellent sound and heat insulation.

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	18	18
m ² per pack	4.66m ²	3.90m ²
Weight per pack	15.64kg	13.26kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2mm	ISO 24346:2006-10
Wear Layer	0.3mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance /Tog Rating	0.01m ² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23 – Heavy Domestic Class 31 – Light Commercial	EN ISO 10874
Inflammability	Bfl-s1	EN 13501
Scratch Resistance	MSR-A2, MSR-B2	EN ISO 16094
Squareness & Straightness	≤ 400 mm: ≤ 0.25 mm > 400 mm: ≤ 0.35 mm	EN ISO 24342:2018-11
Slip Resistance	DS/R10	EN 13893
Residual Indentation	Norm:≤ 0.1mm Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	4 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	15 Year Residential 5 Year Commercial	



Backed with a comprehensive warranty for life's unexpected changes.



Letting you put 100% into your house move. Zero hassle. Zero stress. Every time.



Choosing the right flooring for each room is a breeze with our RoomViewer app.