

Bellatour

Available in the following styles



Golden Timber
APX4101



Rustic Maple
APX4102



Autumn Grove
APX4103




Cedar Ridge
APX4104



Amber Elm
APX4105



Stained Pine
APX4106



Arctic Birch
APX4107



Bronzed Timber
APX4108



Shadow Birch
APX4109




Toasted Oak
APX4110




Copper Pine
APX4111




Silver Maple
APX4112




Sierra Stone
APX4113



Speckled Dune
APX4114



Calcium Stone
APX4115



Ender Slate
APX4116

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	18	18
m² per pack	4.66m²	3.90m²
Weight per pack	15.64kg	13.26kg
PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2mm	ISO 24346:2006-10
Wear Layer	0.3mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance /Tog Rating	0.01m² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23 - Heavy Domestic Class 31 - Light Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501
Scratch Resistance	MSR-A2, MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25 mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/R10	EN 13893
Residual Indentation	Norm:≤ 0.1mm Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	4 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	15 Year Residential 5 Year Commercial	

