



Illuma Deluxe

Available in the following styles




Amber Veil
APX2401



Soft Taupe
APX2402




Midnight Flight
APX2403




Stormed Slate
APX2404




Pale Summit
APX2405




Frosted Azure
APX2406



Butterfly Silk
APX2407




Ivory Glaze
APX2408



Shadow Oak
APX2409



Azure Dream
APX2410



Emerald Radiance
APX2411



Autumn Drift
APX2412



CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	100% Recycled Polyester, 2 Ply	
Machine Gauge	1/10 gauge	
Width	4 & 5 Mtrs	
Tufts Density	173,228 tufts/ m ²	BS ISO 1763:2020
Total Weight	3180g	BS ISO 8543:2020
Inserted Weight	2400g	BS ISO 8543:2020
Pile Height	10mm (±10%)	BS ISO 1766:1999
Total Thickness	12mm (±10%)	BS ISO 1765:1986
Standard Roll Length	25 linear metres	
Type of Backing	Combi Back®	
Classification	Class 23 - Heavy Domestic Class 32 - Moderate Commercial	BS EN 1307:2014
	Luxury Class 5	BS EN 1307:2014
Thermal Resistance	1.44 tog / 0.144 m ² K/W	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	High Radius of Char	BS 4790:1987 (2014)
Flammability	Efl-s1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12
WARRANTY		
Wear	10 Years	
Stain	Bleach Cleanable	
Biological	Moth Proof/Insect Proof	
Made in the UK		
CE Compliant		EN14041:2004
ISO Certifications		ISO 9001, ISO 14001, ISO 45001

