

Illuma Elite

Available in the following styles



Amber Veil
APX2301



Soft Taupe
APX2302




Midnight Flight
APX2303




Stormed Slate
APX2304



Pale Summitt
APX2305



Frosted Azure
APX2306



Butterfly Silk
APX2307



Ivory Glaze
APX2308



Shadow Oak
APX2309



Azure Dream
APX2310



Emerald Radiance
APX2311



Autumn Drift
APX2312

CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	100% Recycled Polyester, 2 Ply	
Machine Gauge	1/10 fauge	
Width	4 & 5 Mtrs	
Tufts Density	162730 tufts/ m²	BS ISO 1763:2020
Total Weight	2380g	BS ISO 8543:2020
Inserted Weight	1600g	BS ISO 8543:2020
Pile Height	8mm (±10%)	BS ISO 1766:1999
Total Thickness	10mm (±10%)	BS ISO 1765:1986
Standard Roll Length	30 linear meters	
Type of Backing	Combi Back®	
Classification	Class 23 - Heavy Domestic Class 32 - Moderate Commercial	BS EN 1307:2014
	Luxury Class 5	BS EN 1307:2014
Thermal Resistance	1.31 tog / 0.131 m² K/W	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	High Radius of Char	BS 4790:1987 (2014)
Flammability	Efl -s1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12
WARRANTY		
Wear	10 Years	
Stain	Bleach Cleanable	
Biological	Moth Proof/Insect Proof	
Made in the UK		
CE Compliant		EN14041:2004
ISO Certifications		ISO 9001 ,ISO 14001, ISO 45001

