

Marsor

Available in the following styles



Amber Edge
APX4201



Sawn Sun
APX4202



Fine Oak
APX4203



Foggy Chestnut
APX4204



Saharan Timber
APX4205



Rustic Straw
APX4206



Bourbon Pine
APX4207



Maple Drift
APX4208



Sundown Timber
APX4209



Emperor Grey
APX4210




Savannah Birch
APX4211




Honey Ember
APX4212




Clustered Martzi
APX4213



Ivory Quarry
APX4214



Frosted Slate
APX4215



Snowflake Quartz
APX4216

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	14	16
m ² per pack	3.62m ²	3.47m ²
Weight per pack	15.19kg	14.37kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2.5mm	ISO 24346:2006-10
Wear Layer	0.55mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance /Tog Rating	0.01m ² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23 - Heavy Domestic Class 33 - Heavy Commercial	EN ISO 10874
Inflammability	Bfl-s1	EN 13501
Scratch Resistance	≤MSR-A2, ≤ MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25 mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/R10	EN 13893
Residual Indentation	Norm:≤ 0.1mm Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	3 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	25 Year Residential 10 Year Commercial	

