


Nebulaura

Available in the following styles




Winter Limestone
APX1701



Dusted Silver
APX1702



Armoured Pewter
APX1703




Cracked Chateau
APX1704



Seabourne Flint
APX1705



Harbour Clay
APX1706




Clotted Dough
APX1707



Founders Grey
APX1708



Ancient Carbon
APX1709



Chia Curnel
APX1710



Buttermere Slab
APX1711



Salted Straw
APX1712

CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted	
Yarn	100% Polypropylene, 2 Plys	
Machine Gauge	1/10 gauge	
Width	4 & 5 Mtrs	
Tufts Density	178,478 tufts/ m²	BS ISO 1763:2020
Total Weight	2700g	BS ISO 8543:2020
Inserted Weight	1800g	BS ISO 8543:2020
Pile Height	10mm (±10%)	BS ISO 1766:1999
Total Thickness	13mm (±10%)	BS ISO 1765:1986
Standard Roll Length	25 linear metres	
Type of Backing	Combi-bac	
Classification	Class 23 - Heavy Domestic Class 33 - Heavy Commercial	BS EN 1307:2014
Thermal Resistance	High Radius of Char	BS 4790:1987 (2014)
Hot Metal Nut Test	1.36 TOG / 0.136m² K/W	BS 4745:2005 (ISO 5085-1:1989)
Flammability	Efl-s1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12
WARRANTY		
Wear	10 years	
Stain	Bleach Cleanable	
Biological	Moth / Insect proof	
Made in UK		
CE Compliant		EN14041:2004
ISO certifications		ISO 9001, ISO 14001, ISO 45001

