


Revive

Available in the following styles



Soft Ivory
APX1201



Golden Horizon
APX1202




Creamy Biscotti
APX1203




Barley Meadow
APX1204



Windswept Bark
APX1205



Frosted Platinum
APX1206



Silk Mist
APX1207



Morning Fog
APX1208



Tarnished Script
APX1209



Ancient Scroll
APX1210



Polished Pewter
APX1211



Dusky Ember
APX1212

CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	100% PP	
Machine Gauge	1/8 Gauge	
Width	4 & 5 Mtrs	
Tufts Density	149000 tufts/ m ²	BS ISO 1763:2020
Total Weight	1815grms	BS ISO 8543:2020
Inserted Weight	925grms	BS ISO 8543:2020
Pile Height	7.5mm (±10%)	BS ISO 1766:1999
Total Thickness	10mm (±10%)	BS ISO 1765:1986
Standard Roll Length	30 linear meters	
Type of Backing	Combi-bac®	
Classification	Class 21- Moderate Domestic Luxury Class 3	BS EN 1307:2014
Thermal Resistance	1.38 TOG / 0.138m ² K/W	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	High Radius of Char	BS 4790:1987 (2014)
Flammability	Efl S1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12
WARRANTY		
Wear	5 years	
Stain	Bleach Cleanable	
Biological	Moth / Insect proof	
Made in the UK		
CE Compliant		EN14041:2004
ISO certifications		ISO 9001 / ISO 14001 / ISO 45001

