

Sirona



Furlong Flooring®
First choice flooring for every room

Product Specification

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	18	18
m ² per pack	4.66m ²	3.90m ²
Weight per pack	15.64kg	13.26kg
PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2 mm	ISO 24346:2006-10
Wear Layer	0.3mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance /Tog Rating	0.01m ² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23- Heavy Domestic Class 31-Light Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501
Scratch Resistance	MSR-A2, MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25 mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/ R9 :R10	EN 13893
Residual Indentation	Norm:≤ 0.1mm Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	4 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	15 Year Residential 5 Year Commercial	



Sirona



Furlong Flooring®
First choice flooring for every room

Product Specification

Sirona LVT flooring authentically captures the character, details, and textures of natural materials, and it comes in various wood and tile designs. It is naturally warm to the touch and provides excellent sound and heat insulation. This range creates a feeling of tranquility in a room

COLOURS	PLANKS	TILES	Slip Resistance
Hamilton Oak	22121		R9
Pulaski Oak	22232		R9
Glade Oak	22315		R9
Cheriton Oak	22325		R9
Alberta Oak	22329		R9
Louisa Oak	22856		R9
Monterey Oak	22934		R9
Keysville Oak	24235		R10
Bloxom Oak	24241		R10
Duffield Oak	24279		R10
Fincastle Oak	24863		R10
Saltville Oak	24961		R10
Kitts Stone		46522	R10
Cruz Stone		46541	R10
Nevis Stone		46561	R10
Tillar Stone		46960	R10



Suitable
for bathrooms



Suitable for use with
underfloor heating



0.3mm
wear layer



Scuff-proof
coating



Residential
Warranty



Slip resistant
*depending on
decor please check
table

Dartford: 01322 628700

Preston: 01772 316150

Stonehouse: 01452 228400

Ireland +353-1-409200

www.furlongflooring.com

enquiries@furlongflooring.com

