

# Vallorium

Available in the following styles



Coastal Oak  
APX4301




Forest Wood  
APX4302




Classic Trunk  
APX4303



Sunset Teak  
APX4304




Sage Birch  
APX4305




Heritage Oak  
APX4306




Canyon Walnut  
APX4307



Alpine Marble Square  
APX4308




Venetian Marble Square  
APX4309




Coastal Oak HB  
APX4310




Forest Wood HB  
APX4311




Classic Trunk HB  
APX4312




Sunset Teak HB  
APX4313




Sage Birch HB  
APX4314



Heritage Oak HB  
APX4315



Canyon Walnut HB  
APX4316



Alpine Marble Rectangle  
APX4317



Venetian Marble Rectangle  
APX4318

| PRODUCT DIMENSIONS        | PLANK              | HERRINGBONE       | SQUARE TILE       | MEDIUM TILE        |
|---------------------------|--------------------|-------------------|-------------------|--------------------|
| Width                     | 196mm              | 158mm             | 493mm             | 493mm              |
| Length                    | 1320mm             | 632mm             | 493mm             | 986mm              |
| Number of panels per pack | 14                 | 24                | 14                | 10                 |
| m <sup>2</sup> per pack   | 3.62m <sup>2</sup> | 2.4m <sup>2</sup> | 3.4m <sup>2</sup> | 4.86m <sup>2</sup> |
| Weight per pack           | 15.09kg            | 9.97kg            | 14.16kg           | 20.27kg            |

| PRODUCT INFORMATION            |                                                          | PRODUCT SPECIFICATION |  |
|--------------------------------|----------------------------------------------------------|-----------------------|--|
| Construction                   | PVC                                                      |                       |  |
| Thickness                      | 2.5mm                                                    | ISO 24346:2006-10     |  |
| Wear Layer                     | 0.55mm                                                   | EN ISO 24340:2012-02  |  |
| Wear Layer Treatment           | Superguard Pride®                                        |                       |  |
| Thermal Resistance /Tog Rating | 0.01m² K/W / 0.1 Tog                                     | EN 12667:2001-01      |  |
| Suitability                    | Class 23 - Heavy Domestic<br>Class 33 - Heavy Commercial | EN ISO 10874          |  |
| Inflammability                 | Bfl-s1                                                   | EN 13501              |  |
| Scratch Resistance             | MSR-A1, MSR-B1                                           | EN ISO 16094          |  |
| Squareness & Straightness      | ≤400mm: ≤0.25 mm   >400mm: ≤0.35mm                       | EN ISO 24342:2018-11  |  |
| Slip Resistance                | DS/R10                                                   | EN 13893              |  |
| Residual Indentation           | Norm:≤ 0.1mm Average result measured: 0.05mm             | EN ISO 24343-1        |  |
| Furniture Leg Resistance       | No visible damage                                        | EN ISO 16581:2019-06  |  |
| Curling                        | Norm:≤ 2mm. Result: OK                                   | EN ISO 23999          |  |
| Dimensional stability          | Norm: ≤ 0.25 %<br>Average result measured: ≤0.05%        | EN ISO 23999:2021-11  |  |
| Formaldehyde Group             | E1                                                       | EN 717-1              |  |
| Acoustic Insulation            | 3 dB                                                     | EN ISO 717-2          |  |
| Castor Chair Resistance        | No damage to wear layer, no delamination                 | EN ISO 4918           |  |
| Stain Resistance               | OK                                                       | EN ISO 26987          |  |
| Light Fastness                 | Class ≥ 6                                                | EN ISO 105-B02        |  |
| Underfloor Heating             | Suitable, max 27°C                                       | EN 12524              |  |
| Warranty                       | 25 Year Residential<br>10 Year Commercial                |                       |  |

