

Vallorium

Available in the following styles



Coastal Oak
APX4301




Forest Wood
APX4302




Classic Trunk
APX4303



Sunset Teak
APX4304



Sage Birch
APX4305



Heritage Oak
APX4306



Canyon Walnut
APX4307



Alpine Marble Square
APX4308




Venetian Marble Square
APX4309



Coastal Oak HB
APX4310



Forest Wood HB
APX4311



Classic Trunk HB
APX4312




Sunset Teak HB
APX4313



Sage Birch HB
APX4314



Heritage Oak HB
APX4315



Canyon Walnut HB
APX4316



Alpine Marble Rectangle
APX4317



Venetian Marble Rectangle
APX4318

PRODUCT DIMENSIONS	PLANK	HERRINGBONE	SQUARE TILE	MEDIUM TILE
Width	196mm	158mm	493mm	493mm
Length	1320mm	632mm	493mm	986mm
Number of panels per pack	14	24	14	10
m ² per pack	3.62m ²	2.4m ²	3.4m ²	4.86m ²
Weight per pack	15.09kg	9.97kg	14.16kg	20.27kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2.5mm	ISO 24346:2006-10
Wear Layer	0.55mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pride®	
Thermal Resistance /Tog Rating	0.01m ² K/W / 0.1 Tog	EN 12667:2001-01
Suitability	Class 23 - Heavy Domestic Class 33 - Heavy Commercial	EN ISO 10874
Inflammability	Bfl-s1	EN 13501
Scratch Resistance	MSR-A1, MSR-B1	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25 mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/R10	EN 13893
Residual Indentation	Norm:≤ 0.1mm Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm:≤ 2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25 % Average result measured: ≤0.05%	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	3 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	25 Year Residential 10 Year Commercial	

